



CAM-NUMBERPLATE-2 Number Plate Camera Frame

PRODUCT FEATURES:

Image Sensor: 1099 HD CCD
Resolution: 976 x 496
TV Lines: 480
Horizontal Angle: 170 Degrees
Vertical Angle: 120 Degrees
TV System: NTSC/PAL
Lumen: 0.1 Lux
LED's: 16x White Illumination LED's
Video Output: 1.0V p-p 75ohm
Operating Voltage: 12V DC (Negative Ground)
Current Consumption: 110mA @ 13.8V
Waterproof Rating: IP68
Operating Temperature: -20 Degrees C to +70 Degrees C
Parking Lines: Yes
Removable Lines: Yes
Image Adjustment: Yes (Mirror/Normal)
Enhanced Performance In Low Light: Yes
Number Plate Surround Size: 550mm x 140mm

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Number plate surround with camera and 90cm cable to mini Male 6pin connector
- Camera connection cable with mini Female 6pin connector, RCA Female connector and 1m DC power cable
- 6m Male to Male RCA extension cable
- Instructions

INSTALLATION

1. Remove the rear number plate from the vehicle and secure it to the number plate surround.
- 2 Attach the surround to the vehicle and connect the 6pin connector to the camera connection cable.
3. Connect the Black wire to a suitable ground and the Red wire to the reversing light circuit or an interface that provides a reverse signal.
4. Connect the camera connection cable to the display monitor using the 6m extension cable and ensure that the image is displayed correctly.
5. Adjustment of the camera may be required to ensure that the correct angle of the image is achieved and that the distance markers on the parking lines correspond to that of the object in view.
6. If adjustment of the camera is required, loosen the 2x grub screws and set the camera in the required position.
7. To swap the image from mirror to normal view, cut the small White looped wire which is located on the camera connection cable.
8. To remove the parking line feature, cut the small Blue looped wire which is located on the camera connection cable.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2