



Z1502i - 2 Channel class A/B Amplifier

Z series Amplifiers have been renewed and completely repackaged with an improved design. The legacy Z series has always been known for its rock solid design and performance. We didn't want to change that, but we wanted to make some improvements, which meant that we completely redesigned the circuit board to make the amplifier smaller. We also managed to get some more performance from the amplifiers, so much that these amps are now our most underrated amplifier series.

Z series Amplifiers - contains 3 models, 2ch, 4ch and a mono amplifier. Even though it's our starting series, it's packed with features from its bigger brother ZR series. Some of the features include High level input with an Autostart function, along with all the filter functions and a differential input design to avoid any unwanted noise on the input signal. The Z3001 comes with a sleek looking gain controller in the box so no need to buy as accessories. The amplifier is fan cooled for one reason... to never let the owner down, it will keep working in almost any conditions.

Technical

- CLASS AB Design
- Simplified Circuit
- Rock solid performance and quality
- High Level input on RCA
- Balanced differential input design
- Autostart on High Level input
- Balanced differential input design
- Full colour print
- Fan cooled for continued operation in hot conditions
- Min 10% power margin (300W delivers over 450W RMS in low load)
- Remote gain controller made clever (Z3001i)
- Short, Thermal, Overload Protection circuits

Specifications

- Compact Class A/B 2-Channel Amplifier
- Power (MAX) 400W Power Ratings (RMS)
- 70W x 2 @ 4Ohm
- 100W x 2 @ 2Ohm
- 200W x 1 @ 4Ohm bridged
- Frequency Response 20Hz - 20kHz
- Signal to Noise Ratio >96dB
- High & Low Pass Crossover 6dB per Octave
- Crossover Range 50Hz - 400Hz
- Bass Boost @ 45Hz 0 to +18dB
- Low - High Level Input Range 0.2V to 10V
- Minimum Load Impedance 2ohm stereo & 4ohm bridged
- Dimensions (L x W x H) 184 x 160 x 48mm



Part Number	Description	EAN Code	Unit Weight	Masterpack Weight	Masterpack
Z1502i	4ch Amplifier	5056171534368	1,45	7,2	5



Z3001i - 1 Channel class A/B Amplifier

Z series Amplifiers have been renewed and completely repackaged with an improved design. The legacy Z series has always been known for its rock solid design and performance. We didn't want to change that, but we wanted to make some improvements, which meant that we completely redesigned the circuit board to make the amplifier smaller. We also managed to get some more performance from the amplifiers, so much that these amps are now our most underrated amplifier series.

Z series Amplifiers - contains 3 models, 2ch, 4ch and a mono amplifier. Even though it's our starting series, it's packed with features from its bigger brother ZR series. Some of the features include High level input with an Autostart function, along with all the filter functions and a differential input design to avoid any unwanted noise on the input signal. The Z3001 comes with a sleek looking gain controller in the box so no need to buy as accessories. The amplifier is fan cooled for one reason... to never let the owner down, it will keep working in almost any conditions.

Technical

- CLASS AB Design
- Simplified Circuit
- Rock solid performance and quality
- High Level input on RCA
- Balanced differential input design
- Autostart on High Level input
- Balanced differential input design
- Full colour print
- Fan cooled for continued operation in hot conditions
- Min 10% power margin (300W delivers over 450W RMS in low load)
- Remote gain controller made clever (Z3001i)
- Short, Thermal, Overload Protection circuits

Specifications

- Compact Class A/B Monoblock Amplifier
- Power (MAX) 600W Power Ratings (RMS)
- 200W x 1 @ 4Ohm
- 340W x 1 @ 2Ohm Frequency Response 20Hz - 250Hz
- Signal to Noise Ratio >96dB
- High & Low Pass Crossover 12dB per Octave Crossover Range 50Hz - 250Hz
- Bass Boost @ 45Hz 0 to +12dB
- Low - High Level Input Range 0.2V to 10V Subsonic Filter 12dB per Octave
- Subsonic Crossover Range 10Hz - 55Hz Minimum Load Impedance 2ohm
- Dimensions (L x W x H) 254 x 160 x 48mm
- Includes Bass Controller



Part Number	Description	EAN Code	Unit Weight	Masterpack Weight	Masterpack
Z3001i	1ch Amplifier	5056171534375	4,9	9,7	5



Z3004i - 4 Channel class A/B Amplifier

Z series Amplifiers have been renewed and completely repackaged with an improved design. The legacy Z series has always been known for its rock solid design and performance. We didn't want to change that, but we wanted to make some improvements, which meant that we completely redesigned the circuit board to make the amplifier smaller. We also managed to get some more performance from the amplifiers, so much that these amps are now our most underrated amplifier series.

Z series Amplifiers - contains 3 models, 2ch, 4ch and a mono amplifier. Even though it's our starting series, it's packed with features from its bigger brother ZR series. Some of the features include High level input with an Autostart function, along with all the filter functions and a differential input design to avoid any unwanted noise on the input signal. The Z3001 comes with a sleek looking gain controller in the box so no need to buy as accessories. The amplifier is fan cooled for one reason... to never let the owner down, it will keep working in almost any conditions.

Technical

- CLASS AB Design
- Simplified Circuit
- Rock solid performance and quality
- High Level input on RCA
- Balanced differential input design
- Autostart on High Level input
- Balanced differential input design
- Full colour print
- Fan cooled for continued operation in hot conditions
- Min 10% power margin (300W delivers over 450W RMS in low load)
- Remote gain controller made clever (Z3001i)
- Short, Thermal, Overload Protection circuits

Specifications

- Compact Class A/B 4-Channel Amplifier
- Power (MAX) 600W Power Ratings (RMS)
- 65W x 4 @ 4Ohm
- 90W x 4 @ 2Ohm
- 180W x 2 @ 4ohm bridged
- Frequency Response 20Hz - 20kHz
- Signal to Noise Ratio >96dB
- High & Low Pass Crossover 6dB per Octave
- Crossover Range 50Hz - 400Hz
- Low - High Level Input Range 0.2V to 10V
- Minimum Load Impedance 2ohm stereo & 4ohm bridged
- Dimensions (L x W x H) 254 x 160 x 48mm



Part Number	Description	EAN Code	Unit Weight	Masterpack Weight	Masterpack
Z3004i	4ch Amplifier	5056171534382	2	10,2	5