



...connecting to the aftermarket

# Connects2 Vision

## User Manual

### CAM-VX4

Vauxhall/Opel Reverse Camera  
Vauxhall/Opel Vivaro 2014>

---

#### PRODUCT FEATURES:

Image Sensor: 1/4" CCD

Resolution: NTSC 510 x 492, PAL 500 x 582

TV Lines: 420

Lens: 1.7mm

Viewing Angle: 170 Degrees

Minimum Illumination: 0 Lux (LED's on)

Operating Voltage: 12V DC (Negative Ground)

Current Consumption: 69-117mA @ 13.8V

Operating Temperature: -20 Degrees C to +70 Degrees C

Waterproof Rating: IP68

Infra-Red LED's: Yes

Night Vision Distance: 35ft

Image: Mirror

---

#### DISCLAIMER:

##### Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

**Connects2 can not be held responsible for the installation of this product.**

##### Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

**Please use our dedicated online technical support centre: [support.connects2.com](http://support.connects2.com)**

## CONTENTS

---

- Camera with 65cm cable to Male 4pin camera connector
- 30cm camera connection cable with Female 4pin camera connector to 2x RCA - Female connectors and Female DC power connector
- 1.4m DC power cable with Male DC connector
- 10m 4pin to 4pin extension cable
- Male to Male RCA splice
- Instructions

## INSTALLATION

---

1. Remove the third brake light from the vehicle and unplug the connection cable.
2. Remove the bulb and refit it into the CAM-VX4
3. Connect the connection cable to the CAM-VX4 and refit to the vehicle taking care not to trap any cables.
4. Check for normal function of the third brake light.
5. Connect the camera cable to the 4pin extension cable.
6. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
7. Connect the 4pin extension cable to the camera connection cable and connect the Yellow RCA connector to the display monitor using the supplied RCA splice and ensure that the image is displayed correctly.



Subscribe to our YouTube Channel for installation guides and tips... [www.youtube.com/connects2](http://www.youtube.com/connects2)